



S BAND RECEIVER RTD



Applications : drones, aircrafts, tanks ...

REMOTE CONTROL or TELEMETRY RECEIVER

- Frequency range: 2100 to 2300 MHz.
2300 to 2500 MHz.
- Noise figure: < 2 dB.
- Dynamic input: -20 dBm to -95 dBm.
- Maximum input level : +10 dBm.
- Sensibility: - 90 dBm for 10 dB SINAD.
- Synthesized.
- Programming increments: 125 kHz step.
- Frequency accuracy: ± 15 ppm at 25 °C.
- Frequency stability: ± 20 ppm from -10°C to +70°C.
- Demodulation: FSK FM
- Data rate : ≤ 12 Mbits/s.
- Output : RS232 or RS485 or TTL
(factory setting).

POWER REQUIREMENT

- 12 V DC (11 V min to 16 V max).
or 28 V DC (18 V min to 36 V) (factory setting).
- < 500 mA for 12 V.
- < 500 mA for 28 V.
- Reverse polarity protection.

ENVIRONMENTAL CONDITIONS

- Operating temperature range : -30 to +70° C.
- Vibration: 10 Hz to 400 Hz, 10 g-c.
Random 0.4 g²/Hz from 10 to 400 Hz.
- Shock: ½ sinus 6 ms, 80 g.
- Acceleration: 80 g.
- Watertight: IP54.

DIMENSIONS

- 170 x 111 x 32 (mm).
- Weight : < 500 g.
- RF input connector : SMA.
- Power and output connector : Type « D ».

OPTIONS

- Data subcarrier (on request).
- Other modulations (on request).

**Specifications subject to change without notice*

Distributed by:
AA SYSTEL France
9, rue RAVEL, 91620 NOZAY / France
TEL: + 33 1 6963 8630
FAX: + 33 1 6963 8474
E-mail: wang.huiqin@a-a.fr
Beijing mobile: +86 138 010 11504